

Choosing PAG shows others that you demand the best

Paglight **LED Dimmer** Unit

> For the industry's most versatile camera light



> Why buy a light that is LED only when you could have one that is **HALOGEN, HMI AND LED?**

> Paglight's unique plug-in lamp holder feature was designed to embrace a range of lighting technologies. The new LED system is an extension of this exceptional design concept.

> If you already own a Paglight you now have the option of adding a new plug-in LED Dimmer unit **Model 9997D**.

> If you do not own a Paglight it is now available with the new LED Dimmer unit and a hot-shoe power base of your choice (see over).

Superior Optics

PAG's new LED unit has an output of 850 lux at 2m. The impressive intensity of light over distance has been achieved by focusing the output of the emitters using an integrated lens, and suspending this system within the parabolic reflector of the Paglight. The output can be controlled to produce a steady and clean transition from spot to flood - a testament to the design of the Paglight optical system. No other camera-top light matches the performance or versatility of the Paglight system - which is LED, halogen or HMI.

Output Control

The plug-in LED unit incorporates a dimming facility which provides precise control of light intensity. The spot and flood feature of the Paglight reflector can also be used to control intensity; it floods out to 62° from a spot angle of 22.6°.

Daylight Blend

The colour temperature of the output is a perfect blend with daylight, and can be converted to match halogen light by using LED Conversion Filter Model 9998, incorporated in the LED Rotatable Accessory Kit Model 9959D, which can be fitted to the front of the Paglight.



Low Consumption

Power consumption of this ultra-efficient unit is a mere 11W. The PAG L95e battery will provide almost 9 hours of run-time for this unit alone.

Cool-Running

The unit is designed to dissipate heat from the finned emitter probe using heat transfer chambers, a patented system embodied in the Paglight design. It means that heavy aluminium heat sinks, commonly used in other LED lights, are not required. Even after prolonged use the Paglight lamp head and the LED unit can be handled comfortably.

Versatility

Paglight is without doubt the industry's most versatile camera light. It is the only light specifically designed to embrace a variety of lighting technologies - tungsten halogen, HMI or LED - and to enable easy exchange between them, without the risk of damage to the unit, or injury to the user. Each method of illumination has its place in news gathering and film production, and it is reassuring to know that with the Paglight system you are equipped with the correct method of illumination for any situation.

Paglight LED Field Kit

In addition to the four Paglight LED options opposite, PAG offers an LED Field Kit Model 9825L. The kit includes > 12V Paglight, > LED Dimmer unit, > two halogen lamp holders, > choice of 2 lamps, > rotatable accessory kit (including dichroic filter, diffuser, and barn doors), > tapered barn doors, > LED to halogen conversion filter, > choice of power base, > handle, > camera clamp, > camera shoe plate, > 1/4" Whit. stud > fitted flight case. This kit enables you to take full advantage of Paglight's unparalleled versatility.

Paglight LED Dimmer Unit

Model 9997D

- > 850 lux at 2m
- > Consumes 11W
- > Matches daylight
- > Includes lamp protector



Paglight LED Options

Paglight SX / LED

Model 9966LD

- > SX Power Base with D-Tap connector (lead length 150mm) for use with light output on Sony cameras
- > Includes LED Dimmer unit
- > Filter ring sold separately
- > Includes Stud Adaptor & Shoe Plate



Paglight PP90 / LED

Model 9964LD

- > PP90 Power Base (lead length 500mm) for use with light output on PAGlok Connector
- > Includes LED Dimmer unit
- > Filter ring sold separately
- > Includes Stud Adaptor & Shoe Plate



Paglight Snap-on / LED

Model 9965LD

- > Snap-on Power Base with D-Tap connector (lead length 500mm) for use with light output on Anton-Bauer battery mount
- > Includes LED Dimmer unit
- > Filter ring sold separately
- > Includes Stud Adaptor & Shoe Plate



Paglight XLR-4 / LED

Model 9956LD

- > XLR-4 Power Base (lead length 1.5m) for use with XLR-4 output on Pagbelt NMH
- > Includes LED Dimmer unit
- > Filter ring sold separately
- > Includes Stud Adaptor & Shoe Plate



PAG Ltd.
565 Kingston Road
Raynes Park
London SW20 8SA

T +44 (0) 20 8543 3131
F +44 (0) 20 8540 4116
E sales@paguk.com
www.paguk.com

Available from
Quadrant Digital Solutions, Unit 1 Hawthorn Road
Castle Donington, Derby, DE74 2QR
Sales: 0870 084 1166, Fax: 01332 817778
information@quadrantdigital.co.uk

© 2009 PAG Ltd. PAG is the trademark of PAG Ltd.

Quadrant
DIGITAL SOLUTIONS